



PRODUCT BULLETIN

STAR RUST-ARREST

Acrylic latex specialty coating to prevent
and hide pavement rust spots.

DESCRIPTION

STAR Rust-Arrest is an acrylic based coating that hides and prevents rust spots in asphalt pavements. Without the use of **STAR Rust-Arrest**, rust spots erupt even through sealcoated surfaces. These eruptions eventually will allow moisture and other elements to penetrate prematurely into the asphalt surface causing damage to the surface in the form of cracks, pot holes and surface blemishes. **STAR Rust -Arrest** will not only protect the asphalt surface it will beautify any pavement that has discolored due to rust colors staining the surface. **STAR Rust-Arrest** is a pavement maintenance product that will act as an important part of your regular pavement maintenance schedule providing two distinct benefits - protection of the asphalt surface and prohibition of the staining and damaging rust deposits in iron contaminated asphalt surfaces.

OUTSTANDING FEATURES

- Will prevent rust spotting and improve surface appearance.
- Is easy to use. Use straight from the container. Minimal on-the-job mixing.
- Applied by any conventional method; brush, spray, roller or squeegee.
- Dries in 30 minutes, Cures in 2 to 4 hours.
- Dries to rich black satin finish.
- Economical, covers 125-150 sq. ft/ gallon.
- Safe to store and easy water clean up.
- Use as a black coating by itself or sealcoat after treating the rust spots.

RECOMMENDED USES

On all asphalt surfaces with rust spotting problems; parking lots, airports, gas stations, home driveways, schools, malls, etc.

Use STAR Rust-Arrest as a black out paint to hide old traffic markings.

DILUTION RATE

None. Ready to use as supplied. Reduce with clean potable water, if needed. The drying time will be delayed by the inclusion of additional water.

APPLICATION NOTES

- **Surface Preparation;** Clean the rust spotted areas with a broom or air blower, to remove all adhering dirt and debris. In some cases pressure washing may be necessary to remove difficult contaminating materials and give the Rust-Arrest the opportunity to bind properly with the surface material. It is being applied to. Ensure that the surface is dry prior to application of **STAR Rust-Arrest**. Asphalt must have weathered to rid the surface of oils.
- **Coverage Rate;** Approximately 125 - 150 sq/ft per gallon.
- **Application;** Thoroughly mix the contents and apply on properly prepared surface. Ensure the proper coverage rates. Use brush, roller, squeegee or spray to apply **STAR Rust-Arrest** to treat rust spotted areas. Conventional Spray; use 0.1" tip size, pressures may vary with ambient temperature.
- **Atmospheric Conditions;** Do not apply when rain is in the forecast within 4 hours, preferably 8 hours. Apply only when the ground and ambient temperatures are min. 50 ° F and rising and sustained for at least 8 hrs.
- **Clean up;** Wash tools immediately with water. Discard used containers according to applicable regulations. **KEEP FROM FREEZING.**

PRECAUTIONS

- **Keep out of reach of children**
- Follow all safety instructions for handling and storage.
- Contains refined tar. Read the Material Safety Data Sheet (MSDS).
- Use with adequate ventilation and avoid inhalation of dry overspray.
- Keep the partially used containers tightly closed.

PACKAGING

- 5 Gallon Pails.
- 55 Gallon Lined Drums.
- 275 Gallon Totes.

SHIPPING POINT

Columbus, Ohio and all STAR Plant Locations.

WARRANTY AND DISCLAIMER

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of our products are beyond our control. STAR will not be responsible for any indirect or consequential damages. We will either replace or refund the purchase price in the event products are proved to be defective, at our option.